

Examination light

Outpatient II

The perfect blend of minimal heat output and high color temperature, low-maintenance and top performance.

The Outpatient II is the documented industry leader for examination lights. More physicians choose the Outpatient II than any other light for focusable flood-type light, maximum intensity and shadow-free operation. With minimal heat output and high color temperature, the Outpatient II is the perfect low-maintenance, top performing light for nearly every application in the hospital or physician's office.

Features

- 86,000 lux (7990 fc) at 24" (61 cm)
- 3300 K color temperature
- CRI (Color Rendering Index) of 94
- Focuses with central removable, autoclavable SteriHandle
- Friction knob allows user to adjust friction on the self-balancing arm positioning to desired tension without a tool
- Cool operation ensured with heat filters and dichroic coatings
- Shadow-free operation provided by three 50-watt halogen bulbs, each with 2000-hour average bulb life
- Bulbs are wired in parallel to ensure continuous operation
- Design allows removal or replacement of SteriHandle with one hand (for ensuring sterile procedures)
- Floorstand units include footswitch, locking casters and cord wrap
- Mounting systems meet California Seismic Codes
- 120V model standard; 230 / 240V models also available
- UL/IEC 60601-1, IEC 60601-1-2, EN/IEC 60601-2-41 and CAN/CSA C22.2 NO. 601.1 M90 certified
- 5-year limited warranty
- Assembled in USA



Ordering information

120V Model	230/240V Model	230/240V SP Model*	100V Model	Description
OP216FL	OP225FL	O202FL25	OP215FL	Floorstand
OP216SC	OP225SC	O202SC25	OP215SC	Single ceiling mount
OP216DC	OP225DC	O202DC25	OP215DC	Double ceiling mount
OP216W	OP225W	O302W25	OP215W	Wall mount
OP216ST	OP225ST		OP215ST	Single Fastrac mount
OP216DT	OP225DT		OP215DT	Double Fastrac mount
Accessories				
0006130PK				Outpatient II replacement bulbs, 3/box
1008465				Outpatient II handle replacement
0008100PK				Light handle covers, sterile, 25/box
1008259				42" drop tube
1008060				Special length, max. 58" drop tube

*SP Model refers to Spanish Language Manuals.