

TR90 TOUGHRAY

ELECTRONIC DESIGN	Computer-controlled, high frequency, full-wave rectified
X-RAY OUTPUT WITH NORMAL INPUT VOLTAGE	30/18 mA @ 40-60 kVDC, 25/15 mA @ 62-70 kVDC, 20/12 mA @ 72-80 kVDC, 15/9 mA @ 82-90 kVDC
X-RAY OUTPUT WITH LOW INPUT VOLTAGE	15/9 mA @ 40-60 kVDC, 12.5/7.5 mA @ 62-70 kVDC, 10/6 mA @ 72-80 kVDC, 7.5/4.5 mA @ 82-90 kVDC
AC INPUT	120 or 230 V; 50/60 Hz; specify voltage desired
LINE VOLTAGE ADJUSTMENT	Automatic, dynamic with low voltage operation system
TIMER	.02-2 sec as follows: .024 sec (.01 sec steps); .4-1.0 sec (.02 sec steps);1.0-1.5 sec (.05 sec steps); 1.5-2.0 sec (.10 sec steps)
INTERNAL POWER SUPPLY	50 kHz High Frequency Inverter System
X-RAY TUBE	XDT-F90-0.8 SNM instruments factory
FOCAL SPOT SIZE	0.8 mm
FOCAL SPOT SIZE ANODE HEAT STORAGE	0.8 mm 7 kHU
ANODE HEAT STORAGE	7 kHU
ANODE HEAT STORAGE TOTAL FILTRATION	7 kHU 2.7 mm Al equivalent Mikasa Model R-300V, continuously adjustable light beam type with adjustable dual integrated laser pointers to indicate central ray and distance in bright ambient
ANODE HEAT STORAGE TOTAL FILTRATION COLLIMATOR	7 kHU 2.7 mm Al equivalent Mikasa Model R-300V, continuously adjustable light beam type with adjustable dual integrated laser pointers to indicate central ray and distance in bright ambient light conditions Class Illa; laser diode; max. output less
ANODE HEAT STORAGE TOTAL FILTRATION COLLIMATOR LP4 LASER POINTERS	7 kHU 2.7 mm Al equivalent Mikasa Model R-300V, continuously adjustable light beam type with adjustable dual integrated laser pointers to indicate central ray and distance in bright ambient light conditions Class Illa; laser diode; max. output less than 2.2 mW, wavelength 635 mm
ANODE HEAT STORAGE TOTAL FILTRATION COLLIMATOR LP4 LASER POINTERS EXPOSURE SWITCH	7 kHU 2.7 mm Al equivalent Mikasa Model R-300V, continuously adjustable light beam type with adjustable dual integrated laser pointers to indicate central ray and distance in bright ambient light conditions Class Illa; laser diode; max. output less than 2.2 mW, wavelength 635 mm Two stage deadman type
ANODE HEAT STORAGE TOTAL FILTRATION COLLIMATOR LP4 LASER POINTERS EXPOSURE SWITCH EXPOSURE CORD	7 kHU 2.7 mm Al equivalent Mikasa Model R-300V, continuously adjustable light beam type with adjustable dual integrated laser pointers to indicate central ray and distance in bright ambient light conditions Class Illa; laser diode; max. output less than 2.2 mW, wavelength 635 mm Two stage deadman type 8 ft (2.4 m)
ANODE HEAT STORAGE TOTAL FILTRATION COLLIMATOR LP4 LASER POINTERS EXPOSURE SWITCH EXPOSURE CORD POWER CORD	7 kHU 2.7 mm Al equivalent Mikasa Model R-300V, continuously adjustable light beam type with adjustable dual integrated laser pointers to indicate central ray and distance in bright ambient light conditions Class Illa; laser diode; max. output less than 2.2 mW, wavelength 635 mm Two stage deadman type 8 ft (2.4 m) 20 ft (6.1 m) 7.4 x 6.2 x 12.3 in



Ordering Information

TR90 Tough Ray High Frequency Portable X-ray Unit

30-9mA @ 40-90 kVDC with carrying case and lightbeam collimator with integrated adjustable dual laser pointers, exposure switch and cord, and power cord.

X100S

Tripod stand

X100SCC

Carrying bag for X100S tripod

EFBTR

Redden equine footblock for TR90 Tough Ray

For more information about MinXray products, contact your local dealer or MinXray at:

MinXray, Inc. 3611 Commercial Avenue Northbrook, Illinois 60062 USA 1-847-564-0323 Toll Free: 1-800-221-2245 (U.S. & CA.) E-mail: info@minxray.com Web: www.minxray.com



