



BOVIE[®] 1250S-VS, ELECTROSURGICAL SYSTEM WITH SMOKE EVACUATION

The Bovie 1250S-V, Specialist | PRO, 120 watt electro-surgery generator combined with the Smoke Shark[™] II smoke evacuator provides a complete and precise energy system with safe and effective smoke particle capture capabilities. Surgical smoke is a by-product of electro-surgery and can carry viruses, CO and other chemical and biological hazards.



Bovie 1250S-V Electro-surgical Generator

- Five modalities with up to 120 watts of power for a variety of tissue effects
- Monopolar and bipolar capabilities
- Compatible with most industry-standard accessories
- Opportunity for additional revenue streams
- 4-year warranty



ESMS-C
Electrosurgical
Mobile Stand with
Smoke Shark[™]
System (SE02)



- The easy-to-use Bovie Smoke Shark II Smoke Evacuator uses a 35-hour, four-stage filter (Pre-filter, ULPA, 24oz Carbon, Post-filter), to effectively capture smoke and particles at the surgical site, down to 0.01mm with 99.99995% efficiency.
- Using smoke evacuation reduces the exposure risk to contaminants at the surgical site lessening the risk of SSIs.
- The system includes a mobile stand with instrument tray and is ideal for the veterinary office, clinic and surgery center.

BOVIE® 1250S-VS, ELECTROSURGICAL SYSTEM WITH SMOKE EVACUATION

EQUIPMENT INCLUDED



Product code: A1250S-VS

Standard Equipment

- **Bovie 1250S-V Electrosurgical Generator**
 - 1 Power Cord
 - 1 ESPR2 Sterile Reusable Pencil
 - 5 Non-Sterile Reusable Electrodes (2 ES01R Blades, 2 A833R Needles, 1 ES20R Ball)
 - 1 A1204P Metal Plate
 - 2 A1254C Grounding Cords
 - 1 MC-55-237-001_r0 User's Guide*
- **Smoke Shark™ system**
 - SE02 Smoke Shark with Pneumatic Footswitch
 - SF35 35-Hour Filter
 - 786T 7/8" (22.225mm) Tube 6' (182.9cm) Long
- **ESMS-C electrosurgical mobile stand**
 - ESMS Mobile Stand, with Instrument Drawer
 - ESMS-B2 Bottom Tray

RECOMMENDED ACCESSORIES †



Bovie EZ Link Remote Activation Switch (SERS2)

*Not Pictured †Sold Separately

PRODUCT SPECIFICATIONS

Dimensions

Height: 15.2cm (6 in.)
 Width: 26cm (10.25 in.)
 Depth: 30.5cm (12 in.)
 Weight: < 4 kg (< 9 lbs.)

Output Power

Cut: 120 watts
 Blend: 90 watts
 Coagulation: 80 watts
 Fulguration: 40 watts
 Bipolar: 30 watts

Output Frequency

350 – 600 kHz

Line Voltage

A1250S-V: 100-240 VAC

Line Frequency

50 – 60 Hz

Warranty: FOUR YEARS



5115 Ulmerton Road, Clearwater, FL 33760 • U.S. Phone 1-800-537-2790 • Fax 1-800-323-1640
 Int'l. Phone +1-727-384-2323 • Fax +1-727-347-9144 • sales@boviemed.com
www.boviemedical.com/a1250s-vs